

Product Range :	Exposed Bath and Shower Mixer			
Product Type :				
Model :	HT-ME-168CR	HT-ME-022CR	HT-EG-022CR	HT-EG-168CR

Pre-installation	Cut-out Dimension Diagram
<ul style="list-style-type: none"> ● Before installation, please ensure that the following work conditions are adhered to: <ul style="list-style-type: none"> - Water temperature between 0°C - 90°C - Water pressure between 0.05MPa – 1.0MPa. Pressure reducing valve is necessary if pressure exceeds 1.2MPa - Avoid major pressure differences between hot and cold water supply ● Flush pipes thoroughly before and after installation to ensure water supply is free of any debris. ● Inspect tap fitting and debugged to its best. Do not attempt to disassemble fitting on your own. ● Use thread sealant tape (PTFE) on any screw joining connections and ensure all joints are securely tightened. 	<p>A tape B wall C fix screw D rosette E rubber mat F hexagon nut G body</p>

Installation Steps
<ol style="list-style-type: none"> 1. Install pipe in bath room wall in advance and connect water flow to clear up pipes (to prevent block, leak or valve spool from being destroyed by sundries). Inlet hole must be 900-1000mm away from the floor and the distance between two holes should be 150±2mm (keep the two holes in a straight line). When facing the wall, the hot water must be on the left while cold water on the right. 2. Bind tape(A) around the fixed screw(C) and fit the fix screw(C) into the holes with a spanner. Then fit the rosette(D) into fix screw(C). 3. Put the rubber mat(E) on the fix screw(C) and install the shower valve body or bath tap into the fix screw(C) with a spanner.

WARRANTY: <ul style="list-style-type: none"> ▪ Lifetime warranty on Anti-rust ▪ 5-year warranty on tap cartridge ▪ 1-year warranty on manufacturing defects 	PRODUCT WARRANTY REGISTRATION: <ul style="list-style-type: none"> ▪ Log on to www.haustern.com for product warranty registration and more information on terms and conditions ▪ Product serial number 818-0114-00001
---	--

CLEANING RECOMMENDATION:
<ul style="list-style-type: none"> ▪ Tap should not be cleaned with abrasive materials such as steel wool or scourers ▪ Do not use any corrosive or abrasive cleaning agents containing acid or scouring agents

This specification is subject to change without notice. FIAMMA TRADING SDN. BHD. will not be held responsible for the use of superseded or voided specifications. Fabricator must check for cut-out accuracy.