

Product Range :	Kitchen Stainless Steel Faucets		
Product Type :	Water Filtration Faucets		
Model :	HT-MX-316/FUCR	HT-MX-317/FUCR	

Pre-installation	Cut-out Dimension Diagram																
<ul style="list-style-type: none"> <li>● Before installation, please ensure that the following work conditions are adhered to: <ul style="list-style-type: none"> <li>- Water temperature between 0°C - 90°C</li> <li>- Water pressure between 0.05MPa – 1.0MPa. Pressure reducing valve is necessary if pressure exceeds 1.2MPa</li> <li>- Avoid major pressure differences between hot and cold water supply</li> </ul> </li> <li>● Flush pipes thoroughly before and after installation to ensure water supply is free of any debris.</li> <li>● Inspect tap fitting and debugged to its best. Do not attempt to disassemble fitting on your own.</li> <li>● Use thread sealant tape (PTFE) on any screw joining connections and ensure all joints are securely tightened.</li> </ul>	<p>The diagram illustrates the faucet's installation into a sink top or work top. It shows the tap body (A) with a rubber O-ring (B) and a tri-bracket (D). The faucet is secured with a rubber O-washer (E) and a metal O-washer (F). A threaded fixing bushing (G) is used to secure the faucet to the sink. Two connection options are shown: Option 1 uses a G1/2" hose with a rubber O-ring (J) and a hose connection (K). Option 2 uses a plastic pipe with a white plastic O-ring (M), a black rubber O-ring (N), and a pipe connection (P). A short white plastic pipe (L) is also shown for connection.</p> <table border="1"> <tr> <td>A Tap Body</td> <td>I Rubber O-ring for flexi hose</td> </tr> <tr> <td>B Rubber O-ring</td> <td>J Black rubber O-Ring</td> </tr> <tr> <td>C Sink top or Work top</td> <td>K Hose connection</td> </tr> <tr> <td>D Tri-Bracket</td> <td>L Short white plastic pipe</td> </tr> <tr> <td>E Rubber O-washer</td> <td>M White plastic O-Ring</td> </tr> <tr> <td>F Metal O-washer</td> <td>N Black rubber O-Ring</td> </tr> <tr> <td>G Threaded fixing bushing</td> <td>P Pipe connection</td> </tr> <tr> <td>H Flexi hose</td> <td></td> </tr> </table>	A Tap Body	I Rubber O-ring for flexi hose	B Rubber O-ring	J Black rubber O-Ring	C Sink top or Work top	K Hose connection	D Tri-Bracket	L Short white plastic pipe	E Rubber O-washer	M White plastic O-Ring	F Metal O-washer	N Black rubber O-Ring	G Threaded fixing bushing	P Pipe connection	H Flexi hose	
A Tap Body	I Rubber O-ring for flexi hose																
B Rubber O-ring	J Black rubber O-Ring																
C Sink top or Work top	K Hose connection																
D Tri-Bracket	L Short white plastic pipe																
E Rubber O-washer	M White plastic O-Ring																
F Metal O-washer	N Black rubber O-Ring																
G Threaded fixing bushing	P Pipe connection																
H Flexi hose																	

Installation Steps
<ol style="list-style-type: none"> <li>1. An opening hole of 35mm diameter is required on sink top or work top (C) for installation of tap.</li> <li>2. Slide the rubber O-ring (B) over the threaded tube and up to the base of tap (A).</li> <li>3. Insert the threaded tube through the hole of sink top or work top (C) and position the tap properly.</li> <li>4. Slide the rubber O-washer (E) and metal O-washer (F) over the threaded tube and up to the underside of sink top or work top (C).</li> <li>5. Screw the fixing bushing (G) up to the metal O-washer (F).</li> <li>6. Connect the flexi hoses (H) to the extension tube on one end and the hot or cold water supply on the other end. Please ensure that the hot water supply goes through the hot flexi hose while the cold water supply goes through the cold flexi hose.</li> </ol> <p>There are two options for connection with drinking water.</p> <p>Option 1 – when drinking water is running through in a G1/2" hose: Please put (J) inside (K) and then connect to the hose tightly.</p> <p>Option 2 – when drinking water is running through in a plastic pipe: Please put the plastic pipe through (P), (N), (M), then connect with (L).</p>

WARRANTY:
<ul style="list-style-type: none"> <li>▪ Lifetime warranty on Anti-rust</li> <li>▪ 5-year warranty on tap cartridge</li> <li>▪ 1-year warranty on manufacturing defects</li> </ul>

PRODUCT WARRANTY REGISTRATION:
<ul style="list-style-type: none"> <li>▪ Log on to <a href="http://www.haustern.com">www.haustern.com</a> for product warranty registration and more information on terms and conditions</li> <li>▪ Product serial number 818-0114-00001</li> </ul>

CLEANING RECOMMENDATION:
<ul style="list-style-type: none"> <li>▪ Tap should not be cleaned with abrasive materials such as steel wool or scourers</li> <li>▪ Do not use any corrosive or abrasive cleaning agents containing acid or scouring agents</li> </ul>

*This specification is subject to change without notice. FIAMMA TRADING SDN. BHD. will not be held responsible for the use of superseded or voided specifications. Fabricator must check for cut-out accuracy.*